MINOR 25 DIMENSIONS, WEIGHT, CAPACITIES





*Dimensions representative and may vary according to options selected

GENERAL	GENERAL DATA			
GVW	4.5 Tonnes			
Wheelbase	2155mm			
Overall Length*	4230mm			
Overall Height*	2245mm			
Discharge Height	750mm Std, 1600mm Hi-Tip			
Discharge Angle	45 degrees			
Door Opening Angle	90 degrees			
Filter Mesh Type	Perforated Stainless Steel			
Low Pressure Pump Output	23 lpm / 4.8 Bar			
Hydraulic Suction Filtration	125 Micron			
Hydraulic Return Filtration	20 micron			
Fan Pump Displacement	45cc / rev			
Gear Pump(s) Displacement	23cc / rev			
Suction Fan Capacity	6900 ft ³ /min / 195m ³ /min			
Suction Fan Diameter	800mm			
Sweeping Speed	0-16 mph / 0-25 kph			

SWEEPING EQUIPMENT				
Front Brush Diameter	700mm			
Side Brush Diameter	500mm			
Widesweep Brush Diameter	320mm			
Brush Speeds	60-120rpm			
Side/Front Brush Life	80 Working Hours			
Widesweep Life	125 Working Hours			
Suction Tube Diameter	200mm			
Nozzle Width	490mm			

CAPABILITIES			
Hopper Volume**	2.1m³ Nett		
Hopper Volume**	2.5m³ Gross		
Actual Payload Capacity*	Up to 1800kg		
Fuel Tank	60 litres		
Water Tank	450 litres		
Hydraulic Tank	40 litres		

^{**} All Scarab Hopper Capacities are measured in accordance with European Standard EN15429

ENGINE DATA

Type	Max Power/Torque	EU Emissions Level	Aspiration
Deutz TCD 2.9L4	55.4kW/300Nm @ 1200rpm	Stage IIIB	Turbocharged/Intercooled

TECHNICAL SPECIFICATION MINOR 25

Scarab Sweepers Ltd,
Pattenden Lane, Marden,
Kent. TN12 9QD
Tel: +44 (0)1622 831006
Fax: +44 (0)1622 832417

www.scarab-sweepers.com

HYDROSTATIC SYSTEM

Variable speed control to optimise sweep performance Selection of forward/ reverse travel by a single lever Max vehicle speed of 40mph (65kph)* Gradeability up to 25%*

*approx. Dependant on conditions, options and operating mode (Local speed limits for mobile machinery need to be observed).

SUCTION FAN

- 800mm diameter
- Up to 2000rpm, low noise
- Capacity 6900 ft³/min (195m3/min)
- · Stainless Steel standard

SUCTION NOZZLE

- Robust all-steel construction
- 490mm mouth width
- 200mm diameter suction tube
- Adjustable wear-resistant flaps
- Low-Pressure water jets
- Heavy Duty rubber-tyred wheels

BRUSHES

- 700mm diameter polypropylene front brushes optional
- 500mm diameter steel-tined side brushes
- 320mm diameter polypropylenesegmented widesweep
- Variable speed 60-120 rpm dependent on engine speed

HOPPER

- 2.1m³ Nett Hopper Volume, capacity
 2.5m³ constructed entirely of corrosion-resistant stainless steel
- Manually-operated rear door with safety prop
- Twin side loading doors
- Safety hopper prop
- Body drains at rear of hopper
- Stainless Steel swing-down mesh suction filter screen
- Access for suction fan cleaning

HYDRAULIC SYSTEM

- Zinc plated steel piping where possible
- 10 micron filters to ensure maximum protection
- Hydraulic valve block in easilyaccessible location
- 40 litre steel oil tank with 10 micron return filter
- Low oil automatic shut-off with sight glass

WATER SYSTEM

- Electric low pressure water pump for dust suppression
- Solenoid-controlled from the CAN Bus system

WATER TANK

- 450 litre integral stainless steel water tank
- Sight glass with fill level indicator

SWEEPING WIDTHS

Suction Nozzle only	550mm
Suction Nozzle and Side Brush	850mm
Suction Nozzle, Side Brush and Widesweep	1570mm
Front Brush, Suction Nozzle,	

Side Brush and Widesweep 1740mm

Both Front Brushes, Suction Nozzle Side Brush and Widesweep

Dual Sweep, all Brushes

deployed

2340mm

2170mm

OPTIONS

A comprehensive Options List is available for the Minor, including:-

- Front Brushes
- Dual Sweep configuration
- High Pressure Water Pump with low level warning

Please contact the Scarab Sales
Department for more information.

ERGONOMIC CAB

The fully-appointed sound insulated and rubber mounted cab includes cloth upholstered driver's and passenger seats, laminated windscreen and sliding windows in each door plus a lower glazed panel in each door for extra visibility. The cab tips for easy engine access. Heated Seats and Sweeping Mirrors standard equipment.

CAN BUS CONTROL

The Scarab proven CANbus system, in service since 2003, offers a compact panel adjacent to the driver's seat which contains all controls for operating the main sweeper functions. The LCD screen displays relevant operating data and provides system diagnostics and a fault-finding facility. The Satellite control panel – for frequently used operations – is mounted conveniently to hand, and incorporates the forward/reverse selector.

PM CERTIFICATION

The Minor 25 has been awarded a 4* EUnited PM10/2.5 certification.





